

CCM Premier

Our flagship guillotine range.
All models including new "Premier Plus" versions



Product information

The latest and highest specification version of the CCM Premier is the CCM Premier Plus range. Available in all sizes, the CCM Premier Plus includes central lubrication, which means wear-free bearings and longer intervals between servicing, large air side tables for easier paper handling, auto knife function for repeat cutting, and a larger diameter backgauge spindle for faster backgauge action.

As well as a recent restyling to improve ergonomics, the CCM Premier Plus range features a deep clamp opening which accepts more paper to reduce overall cutting time, and infra red slimline light barriers. Safety is also enhanced via the use of an optical cutting safety line.

3 levels of programmability to suit your needs and budget

CCM Premier

Built to last- Much heavier than other manufacturers' guillotines to provide:

LESS VIBRATION • LONGER MACHINE LIFE • IMPROVED-CUTTING ACCURACY

- Fixed bolt holes on knife beam ensure total knife stability
- Totally enclosed knife change with monitored single shear bolt protection, turnbuckle adjustment, makes a fast, safe, easy knife change
- High Speed Blades fitted as standard
- Easy clean chromed air tables for smoother paper movement- eliminates pitting and rusting
- High speed ball bearing spindle/Linear guide
- Deep clamp opening accepts more paper to reduce overall cutting time

- Optical shaft encoder on high speed backgauge for faster operation and totally accurate cutting
- Large side tables for easier paper handling
- Infra red slimline light barriers
- Optical cutting safety line
- Networkable; PC to guillotine, or guillotine to guillotine
- CIP4/JDF
- All spare parts held in UK, no waiting or costly import bills
- 5 valve CE standard Wessel hydraulics
- Improved centralised oiling WEAR FREE BEARINGS
- longer intervals between servicing

Specifications	CCM78	CCM92	CCM115	CCM137	CCM155
Cutting width	780mm	920mm	1150mm	1370mm	1550mm
Clamp opening	128mm	132mm	165mm	165mm	165mm
Feed depth	780mm	920mm	1150mm	1370mm	1550mm
Minimum cut	25mm	25mm	25mm	25mm	25mm
Power required	3Kw3/P	3Kw3/P	4Kw3/P	4Kw3/P	5.5Kw
Net weight	2300Kg	2580Kg	3500Kg	4120Kg	5950kg
Machine width	2070mm	2220mm	2610mm	2880mm	3030mm
Machine depth	2070mm	2400mm	2650mm	2820mm	2990mm
Machine height	1550mm	1550mm	1660mm	1660mm	1760mm
Front table depth	665mm	730mm	715mm	715mm	715mm
Table height	900mm	900mm	900mm	900mm	900mm
Clamp pressure min	150daN 300lb	150daN 300lb	150daN 300lb	150daN 300lb	150daN 300lb
Clamp pressure max	3500daN / 7700lb	3500daN / 7700lb	4500daN / 9920lb	5500daN / 12100lb	5500daN / 12100lb