

Stitcher Heads

Swivel-style

DELUXE STITCHER

COMPANY INC.



Model 26/26D

Capacity - Two sheets to 1/4" (6mm)

Wire Sizes – 21-28 Gauge Round and 21x25 Flat

Crown Sizes Available - 5/16" (8mm),
3/8" (10mm), 1/2" (13mm), 5/8" (16mm)

Minimum Head Centres - 1-7/8" (48mm)
for all material thicknesses



Model 18D

Capacity - Two sheets to 9/16" (14mm)

Wire Sizes - 20-28 Gauge Round, 19x21-1/2,
20x25, 20x24 and 21x25 Flat, Hybar I & II and
.020x. 103 Ribbon Wire

Crown Sizes Available - 3/8" (10mm),
1/2" (13mm), 5/8" (16mm), 3/4" (20mm)

Minimum Head Centres - 3" (75mm)
for all material thicknesses

Side Feed-Style



Model G5

Capacity - Two sheets to 13/64" (5mm)

Wire Sizes Available - 25-28 Gauge Round

Crown Sizes Available - 1/2" (12mm),
13/64" (5mm) Loop

Minimum Head Centres - 1-1/2" (39mm)
up to 1/32" (1mm) material thickness

Model G8

Capacity - Two sheets to 5/16" (8mm)

Wire Sizes Available - 23-28 Gauge Round
and 21x25 Flat

Crown Sizes Available - 1/2" (13mm),
13/64" (5mm) Loop

Minimum Head Centres - 2-3/64" (52mm)
up to 1/16" (1.5mm) material thickness



Model G20

Capacity - Two sheets to 3/4" (20mm)

Wire Sizes Available - 20-28 Gauge Round and
19x21-1/2, 20x25, 21x25 and 20x24 Flat

Crown Sizes Available - 1/2" (14mm),
5/8" (16mm), 13/64" (5mm) Loop

Minimum Head Centres - 2-3/4" (70mm)
up to 3/16" (4mm) material thickness

Stitcher Heads

DB-Style Stitcher Heads

For use on: Muller, Osako and Purlux Stitchers



Model DB45

Capacity – Two sheets to 1/8" (3mm)
Wire Sizes Available - 25-28 Gauge Round
Crown Sizes Available - 7/16" (10mm)
Minimum Head Centres - 1-3/4" (45mm)
for all material thicknesses

The DeLuxe Stitcher DB45 is the latest addition to the Company's line of Muller Martini* Replacement Heads. With its 45 mm Centre to Centre distance, this slim line Stitcher Head can be a great addition to any bindery. The DB45 is perfect for two, three or four-up work, when closeness counts.

The DB45 has a stitching capacity from two sheets to 3 mm, a crown size of 10 mm and a built-in Paper Centreing Guide. The DB45 accommodates round wire sizes 25 through 28.



Model DB75

Capacity – Two sheets to 13/64" (5mm)
Wire Sizes Available - 20-28 Gauge Round
Crown Sizes Available - 1/2" (14mm)
Minimum Head Centres - 3" (75mm)
for all material thicknesses

In accordance with the long tradition of DeLuxe Stitcher innovative manufacturing, the DB75 Stitcher Head was developed as a very reliable and versatile replacement Head for almost every model of Muller Martini*, Osako* and Purlux* saddle-stitching machine. With its heavy-duty construction, the DB75 Head will provide thousands of hours of trouble-free operation.

The DB75 boasts a capacity from two sheets to 5 mm, a crown size of 14 mm, a 75 mm Centre to Centre distance and comes standard with Carbide Cutters. The DB75 accommodates wire sizes 22 through 28 round as well as 21x25 and 20x24 flat.

DELUXE STITCHER

COMPANY INC.



Model DB75V

Capacity - Two sheets to 1/4" (6mm)
Wire Sizes Available - 20-28 Gauge Round
Crown Sizes Available - 1/2" (14mm)
Minimum Head Centres - 3" (75mm)
for all material thicknesses

With such features as a Supporter to help maintain a straight crown as well as a heavy-duty Wire Holder Retaining Spring, a Carbide Clincher Slide, a Hook Guide and even a reversible Driver, the DB75V is truly the right Head for the high volume user.

The DB75V boasts a capacity from two sheets to 6 mm, a crown size of 14 mm, a 75 mm Centre to Centre distance and comes standard with Carbide Cutters and a Supporter Assembly for thicker applications. The DB75V accommodates wire sizes 22 through 28 round as well as 21x25 and 20x24 flat.



Special Application Stitcher Machines

Ministitcher:

Capacity - Two sheets to 1/4" (6mm)
with 25 gauge wire. Two sheets to 1/8" (3mm)
with 21x25 gauge wire
Wire Sizes Available - 23-28 Round and
21x25 Flat. 25 Round Standard
Crown Sizes Available - 5/16" (8mm),
3/8" (10mm), 1/2" (13mm), 5/8" (16mm)

Spare parts and sundries are also available by contacting the spare parts department at Terry Cooper Services.